



The Öhlins kit allows lower ride-height than the height shown in the picture

Issued 23/04/2021



ROAD & TRACK

PRODUCT NEWS

**BMW 2-SERIES** 2013-

**PART NO:** BMS MU00 • **CHASSIS CODE:** F22, F23

*Fits RWD & AWD (xDrive) models*

This is the latest step in the Öhlins Racing automotive philosophy – Road & Track by Öhlins.

A more than 30 year long tradition of high-end racing commitments and state-of-the-art solutions within advanced suspension technology is now available for street cars all over the world. The focus has been clear from the very beginning – superior road handling without sacrificing comfort in your day-to-day transports. The time of compromises is over.

We have also added a clever light-weight design with a majority of the parts in aluminium and on top of that all shocks have suffered through vast corrosion tests according to ISO 9227. The end result is a 2-year limited warranty on all of our products - worldwide.



**GENERAL FEATURES**

- > DFV (Dual Flow Valve)
- > Rebuildable
- > Corrosion salt spray tested (ISO 9227)
- > 2 year limited warranty
- > Springs ordered separately

**FRONT FEATURES**

- > McPherson strut, Upside Down
- > Single bleed adjuster for compression and rebound damping
- > Spring preload adjuster
- > Height adjustable (approx. 20-30 mm lower than standard)
- > Coil springs (rate 80N/mm)
- > Use with original top mounts

**REAR FEATURES**

- > Conventional shock absorber
- > Single bleed adjuster for compression and rebound damping
- > Separate spring preload adjuster
- > Height adjustable (approx. 20-30 mm lower than standard)
- > Coil springs (rate 140 N/mm)
- > Use with original top mounts

**CANCELLATION KIT**

For cars equipped OE with electronic adjustable suspension, also Öhlins cancellation kit should be used. This kit ordered separately.

| PART NO  | KIT              |
|----------|------------------|
| 35020-03 | Cancellation kit |

| PART NO  | SPRING | RATE     |
|----------|--------|----------|
| 48010-23 | Front  | 80 N/mm  |
| 48010-47 | Rear   | 140 N/mm |