

Springs for Öhlins MX & Enduro shock absorber



Part-No.	Length	Inner dia.	Outer dia.	Wire dia.	Rate N/mm	Maximum Stroke
00180-series						
00180-85	180	46		8	36	100
00180-57	180	46		8.25	41	97
00180-67	170	46		8.5	45	91
00180-88	180	46		9	52	94
00180-90	230	46			12-14,3 Prog.	

00181-series

00181-09	200	46		8.5	35	110
00181-10	200	46		8.75	40	110
00181-11	210	46		9.25	45	110

00281-series

00281-11	125	46		7	30	74.3
00281-23	125	46		7.25	35	73.7
00281-12	125	46		7.5	40	72.4

00480-series

00480-01					15-24 Prog.	
----------	--	--	--	--	-------------	--

00596-series

00596-08	270	57		11	48	151
00596-09	270	57		11	50	145
00596-10	270	57		11.25	52	147
00596-11	270	57		11.25	54	143
00596-12	270	57		11.5	56	140
00596-13	270	57		11.5	58	141

00698-series

00698-90	230	57		9	32	132
00698-02	230	57		9.75	36	128
00698-03	230	57		9.75	38	132
00698-04	230	57		9.75	40	129
00698-05	230	57		10	42	131
00698-06	230	57		10	44	130
00698-07	230	57		10.25	46	129
00698-08	230	57		10.25	48	128
00698-09	230	57		10.5	50	126
00698-10	230	57		10.5	52	126
00698-11	230	57		10.5	54	121
00698-12	230	57		10.5	56	116

05174-series

005174-09					35	
-----------	--	--	--	--	----	--

Part-No.	Length	Inner dia.	Outer dia.	Wire dia.	Rate N/mm	Maximum Stroke
06310-series						
06310-01Y	225	61-65	80,5-84,5	9.75	34	140
06310-02Y	230	61-65	81-85	10	36	140
06310-03Y	230	61-65	81-85	10.25	38	140
06310-04Y	235	61-65	81,5-85,5	10.5	40	140
06310-05Y	235	61-65	82-86	10.5	42	140
06310-06Y	240	61-65	82,5-86,5	10.75	44	140
06310-07Y	235	61-65	82,5-86,5	10.75	46	140
06310-08Y	240	61-65	83-87	11	48	140
06310-09Y	245	61-65	83-87	11.25	50	140
06310-10Y	245	61-65	83,5-87,5	11.25	52	140
06310-11Y	250	61-65	84-88	11.5	54	140
06310-12Y	250	61-65	84-88	11.5	56	140
06310-13Y	255	61-65	84,5-88,5	11.75	58	140
06310-14Y	260	61-65	85-89	12	60	140
06310-15Y	255	61-65	85-89	12	62	140
06310-16Y	265	61-65	85,5-89,5	12.25	64	140

06320-series

06320-08Y	205	61-65	81,5-85,5	10.5	48	120
06320-09Y	200	61-65	82-86	10.5	50	120
06320-10Y	205	61-65	82,5-86,5	10.75	52	120
06320-11Y	205	61-65	82,5-86,5	10.75	54	120
06320-12Y	215	61-65	82,5-86,5	10.75	56	120
06320-13Y	215	61-65	83-87	11.25	58	120
06320-14Y	215	61-65	83,5-87,5	11.25	60	120
06320-15Y	210	61-65	83,5-87,5	11.25	62	120
06320-16Y	215	61-65	84-88	11.5	64	120
06320-17Y	215	61-65	84,5-88,5	11.5	66	120
06320-18Y	220	61-65	84,5-88,5	11.75	68	120
06320-19Y	225	61-65	85-89	12	70	120
06320-20Y	225	61-65	85-89	12	72	120
06320-21Y	230	61-65	85,5-89,5	12.25	75	120
06320-24Y	235	61-65	86-90	12.5	80	120
06320-26Y	235	61-65	86,5-90,5	12.75	85	120
06320-29Y	240	61-65	87-91	13	90	120
06320-31Y	245	61-65	87,5-91,5	13.25	95	120
06320-39Y	260	61-65	89-93	14	110	120

06410-series

06410-06Y	265	66	88	11	44	150
06410-07Y	265	66	88.5	11.25	46	150
06410-10Y	265	66	89	11.5	52	150
06410-13Y	265	66	90	12	58	150
06410-14Y	265	66	90.5	12.25	60	150
06410-15Y	265	66	91	12.5	62	150

Part-No.	Length	Inner dia.	Outer dia.	Wire dia.	Rate N/mm	Maximum Stroke
06411-series						
06411-07Y	255	63,5-65,5	85,5-87,5	11	46	145
06411-08Y	255	63,5-65,5	86-88	11.25	48	145
06411-09Y	255	63,5-65,5	86-88	11.25	50	145
06411-10Y	255	63,5-65,5	86,5-88,5	11.5	52	145
06411-11Y	255	63,5-65,5	86,5-88,5	11.5	54	140
06411-12Y	255	63,5-65,5	87-89	11.75	56	140
06411-13Y	255	63,5-65,5	87-89	11.75	58	140
06411-14Y	255	63,5-65,5	87,5-89,5	12	60	140
06411-15Y	255	63,5-65,5	87,5-89,5	12	62	140

06420-series

06420-13Y	250	63	86	11.5	58	120
06420-14Y	250	63	86	11.5	60	120
06420-15Y	250	63	86.5	11.75	62	120
06420-16Y	250	63	86.5	11.75	64	120
06420-17Y	250	63	87	12	66	120
06420-18Y	250	63	87	12	68	120
06420-19Y	250	63	87	12	70	120
06420-21Y	250	63	87.5	12.25	75	120
06420-24Y	250	63	88	12.5	80	120
06420-26Y	250	63	88.5	12.75	85	120