

#### Note!

Please note that there can be small differences between your product and the images in these instructions.

#### Note!

Please note that during storage and transport, especially at high ambient temperature, some of the oil and grease used for assembly may leak and stain the packaging. This will not cause damage to the product, wipe off the excessive oil or grease with a cloth.

#### **Kit Contents** Description Part No Pcs TTX Cartridge Kit FGKA1690 1 TTX Cartridge sticker 00191-34 2 Sticker Öhlins 00197-01 2 07298-01 1 Owner's manual 2 Base plug (with o-rings) 15430-09 15440-01 2 Safety clip 15495-02 6 Spacer Hydraulic stop cup 15456-12 2

#### Note!

Before you install this product, check the kit contents. If anything is missing, please contact an Öhlins dealer.

#### A Warning!

Before you install this product, read the Öhlins Owner's manual. This product is an important part of the vehicle and the vehicle stability.

### TTX Cartridge Kit for Kawasaki KX 85



#### **Mounting Instructions**



## **MOUNTING INSTRUCTIONS**

#### A Warning!

We strongly recommend to let an Öhlins dealer install this product.

#### **▲ Warning!**

If you work with a lifted vehicle, make sure that it is safely supported to prevent it from tipping over.

#### Note!

When you work with this product, see the vehicle service manual for vehicle specific procedures and important data.

#### Note!

Before you install this product clean the vehicle.

#### Note!

Öhlins cartridge kit is not designed to be used with standard vehicle fork springs.

# MOUNTING INSTRUCTIONS

## ADJUSTMENTS

#### A Warning!

Before you ride/drive, always make sure that the setup is according to the recommended setup data. Read about adjustments and setting up in the Öhlins Owner's Manual before you make any adjustments. Contact an Öhlins dealer if you have any questions about setting up.

## SETUP DATA

| Rebound damping         | 15          | clicks |
|-------------------------|-------------|--------|
| Compression damping     | 15          | clicks |
| Spring preload          | 0           | mm     |
| Fluid volume (each leg) | 0,200       | litre  |
| Fluid volume range      | 0,180-0,250 | litre  |
| Öhlins Front Fork fluid | 01330-01    |        |
| Spring preload range*   | 0-6         | mm     |

\*Can be adjusted by adding/removing washer 15495-02.

| FGKA 1690                 |     |     |      |  |
|---------------------------|-----|-----|------|--|
| Rider´s weight<br>kg/lbs* | LOW | MID | HIGH |  |
| 40/88                     | Х   | 2,8 | 3,0  |  |
| 45/99                     | 2,8 | 3,0 | 3,0  |  |
| 50/110                    | 3,0 | 3,0 | 3,2  |  |
| 55/121                    | 3,0 | 3,2 | Х    |  |

Available spring rates 08794-series: -28 and -32.

To get spring rate 3,0: Use spring with 2,8 in one fork leg and 3,2 in the other fork leg.

\*Rider's weight: Rider wearing proper riding gear. Make sure you know your total weight with riding gear. Riding gear weighs between 5 and 10 kg.

Öhlins products are subject to continuous improvement and development, therefore, although these instructions include the most up-to-date information available at the time of printing, minor updates may occur. To find the latest information contact an Öhlins distributor. Please contact Öhlins if you have any questions regarding the contents in this document. Part no. MI\_FGKA1690\_0 Issued 2015-11-18

© Öhlins Racing AB. All rights reserved. Any reprinting or unauthorized use without the written permission of Öhlins Racing AB is prohibited. Öhlins Racing AB Box 722 S-194 27 Upplands Väsby, Sweden Phone +46 8 590 025 00 fax +46 8 590 025 80



#### www.ohlins.com