



Issued 25/03/2021



ROAD & TRACK

PRODUCT NEWS

SEAT LEON 2012-, ST, CUPRA, CUPRA ST, CUPRA R, CUPRA R ST

PART NO: VWS MU21 • **CHASSIS CODE:** MK3, 5F



This is the latest step in the Öhlins Racing automotive philosophy – Road & Track by Öhlins.

A more than 30 year long tradition of high-end racing commitments and state-of-the-art solutions within advanced suspension technology is now available for street cars all over the world. The focus has been clear from the very beginning – superior road handling without sacrificing comfort in your day-to-day transports. The time of compromises is over. All shocks have suffered through vast corrosion tests according to ISO 9227. The end result is a 2-year limited warranty on all of our products - worldwide.

Öhlins Road & Track team has extensively tested a wide variation of springs to find the right balance between road and track use. By testing in different conditions on road as well on track, the listed spring rate is what we strongly recommend you to use.

GENERAL FEATURES

- > DFV (Dual Flow Valve)
- > Serviceable and rebuildable
- > Corrosion salt spray tested (ISO 9227)
- > 2 year limited warranty
- > Springs ordered separately
- > Weight reduction compared to original suspension: -10 kg

FRONT FEATURES

- > McPherson strut (55 mm width), Upside Down
- > Single bleed adjuster for compression and rebound damping
- > Height adjustable (approx. 15 mm lower than standard)
- > Coil springs (70 N/mm)
- > Use with original top mounts

REAR FEATURES

- > Conventional shock absorber
- > Single bleed adjuster for compression and rebound damping
- > Height adjustable (approx. 15 mm lower than standard)
- > Coil springs FWD (70 N/mm), 4WD/ST (80 N/mm)
- > Use with original top mounts



CANCELLATION KIT

For cars equipped OE with electronic adjustable suspension, also Öhlins cancellation kit should be used. This kit ordered separately.

PART NO	DESCRIPTION
35020-15	Cancellation kit DCC

PART NO	SPRINGS	SPRING RATE
48000-19	FRONT	70 N/mm
48010-19	REAR FWD	70 N/mm
48010-23	REAR 4WD/ST	80 N/mm