



# TTX 22 M Universal Side-by-Side 230x57,5mm MTBM 1894

The TTX22M shock absorber is designed to handle the most challenging World Cup Downhill tracks while still providing pedal efficiency for the flat and uphill sections. The twin tube design allows the gas pressure to always backup the low-pressure side of the piston to keep pressure at a controlled level. This ensures consistent damping performance on all types of terrain and improves damping response to give outstanding control of the bike and tire movements.

Low and high speed compression and rebound damping are externally adjustable. Spherical bearings is offered as an option on widths up to 22 mm, reducing friction on the shock during side loads to improve small bump sensitivity.

Available in in metric lengths and strokes as well as Trunnion mount, the TTX22M Custom aftermarket shock absorber is designed to handle the most challenging World Cup Downhill tracks while still providing pedal efficiency for the flat and uphill sections. The twin tube design allows the gas pressure to always backup the low-pressure side of the piston to keep pressure at a controlled level. This ensures consistent damping performance on all types of terrain and improves damping response to give outstanding control of the bike and tire movements.

Low and high speed compression and rebound damping are externally adjustable. Spherical bearings is offered as an option on widths up to 22 mm, reducing friction on the shock during side loads to improve small bump sensitivity. All shocks feature the stability mode. 3rd position on high speed adjuster increase compression damping to reduce suspension movements during less technical climbs.

## Technical Specifications:

Twin-Tube-Technology (TTX)

Specifically designed for Gravity/Enduro segment

Nitrogen pressurized bladder reservoir system

Weight between 423 and 454 g (without spring)

new lightweight springs available

Length 230 mm (9,05 Inch)

Stroke 57,5 mm (2,26 Inch)

Aluminium design, hard anodized

Fully servicable and rebuildable

2 years limited warranty

## Adjustment:

3 clicks high speed compression damping

16 clicks low speed compression damping

7 clicks rebound damping

## Purchased parts package:

1 shock absorber TTX22M

Owners manual

Spring is not included and needs to be ordered seperately.

## Springs:

This damper is designed to be used with lightweight springs 18075-06 to -17 (see product group springs). Springs are available in steps of 4 N/mm (23 lbs/in) and have a maximum tolerance of 1,5%. The reduced weight of a spring is between 230 and 355 g.

## Part number

MTBM 1894

## Fits for Mountain bikes

[Universal MTB Coil Shock \( - \)](#)

## Price and availability

**No longer available**



## Performance Suspension Guide

Not sure what you need or how to set up your bike? The Öhlins Performance Suspension Guide will help you to find the right product and base set up for you bike.

[Open Performance Suspension Guide](#)

The picture shown can deviate from the product delivered.





## **Öhlins Europe**

Gottlieb-Daimler-Straße 25  
53520 Meuspath  
Germany

Phone: +49 (0) 2691 -  
937780  
Fax: +49 (0) 2691 - 9377890  
E-Mail: [info.oeu@driv.com](mailto:info.oeu@driv.com)

## **Office Hours**

Monday to Friday  
08:00 AM to 12:30 PM  
01:30 PM to 05:00 PM

