



TTX 22 M Universal Side-by-Side 7,5x2,0" (190x51mm) MTB 1498

The TTX22M shock absorber is designed to handle the most challenging World Cup Downhill tracks while still providing pedal efficiency for the flat and uphill sections. The twin tube design allows the gas pressure to always backup the low-pressure side of the piston to keep pressure at a controlled level. This ensures consistent damping performance on all types of terrain and improves damping response to give outstanding control of the bike and tire movements.

Low and high speed compression and rebound damping are externally adjustable. Spherical bearings is offered as an option on widths up to 22 mm, reducing friction on the shock during side loads to improve small bump sensitivity.

Available in in metric lengths and strokes as well as Trunnion mount, the TTX22M Custom aftermarket shock absorber is designed to handle the most challenging World Cup Downhill tracks while still providing pedal efficiency for the flat and uphill sections. The twin tube design allows the gas pressure to always backup the low-pressure side of the piston to keep pressure at a controlled level. This ensures consistent damping performance on all types of terrain and improves damping response to give outstanding control of the bike and tire movements.

Low and high speed compression and rebound damping are externally adjustable. Spherical bearings is offered as an option on widths up to 22 mm, reducing friction on the shock during side loads to improve small bump sensitivity. All shocks feature the stability mode. 3rd position on high speed adjuster increase compression damping to reduce suspension movements during less technical climbs.

Technical Specifications:

Twin-Tube-Technology (TTX)

Weight between 425 and 460 g (without spring)

Length 190 mm (7,5 Inch)

Stroke 51 mm (2,00 Inch)

Wheel size

Aluminium design, hard anodized

Fully servicable and rebuildable

2 years limited warranty

Adjustment:

- 3 clicks high speed compression damping
- 16 clicks low speed compression damping
- 7 clicks rebound damping

Purchased parts package:

- 1 shock absorber TTX22M
- Model related parts for mounting
- Owners manual

Spring is not included and needs to be ordered seperately.

Springs:

This damper is designed to be used with springs 18075 (see product group springs). Springs are available in steps of 4 N/mm (23 lbs/in) and have a maximum tolerance of 1,5%. Spare part 18029-03 is need for all spring rates -15 and higher

Part number

MTB 1498

Fits for Mountain bikes

[Universal MTB Coil Shock \(- \)](#)

Price and availability

842,15 €

842,15 € plus % VAT

in stock

(3 - 5 business days)



ADD TO CART



Performance Suspension Guide

Not sure what you need or how to set up your bike? The Öhlins Performance Suspension Guide will help you to find the right product and

base set up for you bike.

[Open Performance Suspension Guide](#)

The picture shown can deviate from the product delivered.





Öhlins Europe

Gottlieb-Daimler-Straße 25
53520 Meuspath
Germany

Phone: +49 (0) 2691 -
937780
Fax: +49 (0) 2691 - 9377890
E-Mail: info.oeu@driv.com

Office Hours

Monday to Friday
08:00 AM to 12:30 PM
01:30 PM to 05:00 PM

