



TTX 22 M MTB 1495

The TTX22M shock absorber is designed to handle the most challenging World Cup Downhill tracks while still providing pedal efficiency for the flat and uphill sections. The twin tube design allows the gas pressure to always backup the low-pressure side of the piston to keep pressure at a controlled level. This ensures consistent damping performance on all types of terrain and improves damping response to give outstanding control of the bike and tire movements.

Low and high speed compression and rebound damping are externally adjustable. Spherical bearings is offered as an option on widths up to 22 mm, reducing friction on the shock during side loads to improve small bump sensitivity.

Ever since the launch of the Öhlins TTX22M in 2013, the shock absorber has created a buzz within the bike industry. Riders have praised the shock from the time it was released.

The TTX22M shock absorber is designed to handle the most challenging World Cup Downhill tracks while still providing pedal efficiency for the flat and uphill sections. The twin tube design allows the gas pressure to always backup the low-pressure side of the piston to keep pressure at a controlled level. This ensures consistent damping performance on all types of terrain and improves damping response to give outstanding control of the bike and tire movements.

Low and high speed compression and rebound damping are externally adjustable. Spherical bearings is offered as an option on widths up to 22 mm, reducing friction on the shock during side loads to improve small bump sensitivity.

Technical Specifications:

- Twin-Tube-Technology (TTX)
- Weight between 425 and 460 g (without spring)
- Length 241 mm (9,5 Inch)
- Stroke 76 mm (3,0 Inch)
- Wheel size
- Aluminium design, hard anodized
- Fully servicable and rebuildable
- 2 years limited warranty

Adjustment:

3 clicks high speed compression damping

16 clicks low speed compression damping

7 clicks rebound damping

Purchased parts package:

1 shock absorber TTX22M

Model related parts for mounting

Owners manual

Spring is not included and needs to be ordered seperately.

Springs:

This damper is designed to be used with springs 18060-01 to -11 or leightweight springs 18073-01 to -15 (see product group springs). Springs are available in steps of 4 N/mm (23 lbs/in) and have a maximum tolerance of 1,5%. The weight of a spring is between 650 and 850 g.

Part number

MTB 1495

Fits for Mountain bikes

[Universal MTB Air Fork \(- \)](#)

Price and availability

No longer available



Performance Suspension Guide

Not sure what you need or how to set up your bike? The Öhlins Performance Suspension Guide will help you to find the right product and base set up for you bike.

[Open Performance Suspension Guide](#)

The picture shown can deviate from the product delivered.





Öhlins Europe

Gottlieb-Daimler-Straße 25
53520 Meuspath
Germany

Phone: +49 (0) 2691 -
937780
Fax: +49 (0) 2691 - 9377890
E-Mail: info.oeu@driv.com

Office Hours

Monday to Friday
08:00 AM to 12:30 PM
01:30 PM to 05:00 PM

