



# Air Fork RXF36 M.2 Air 27,5 / Stroke 150 mm / Offset 46 mm

The race proven TTX 18 dampening from the DH Race Fork has been reworked for the all new RXF36 m.2 fork to give optimal traction and control on trails and Enduro race courses. The RXF36 m.2 is available as an Air or Coil fork. The TTX 18 cartridge kit featuring trail-optimized 18 mm piston for improved small bump sensitivity. With increased damping pressure bandwidth the damping valve response and sensitivity has improved.

The damping adjustment range is set specifically for trail to Enduro race use with 15 clicks of low speed compression and low speed rebound. For the high speed compression damping you get 3 clicks plus a climb mode setting. The retuned twin piston three chamber air spring system allows total air spring tuning from the initial movement through to the bottom out.

## Technical Specifications:

- Weight approx. 2050 g
- Length 550 mm (axle to crown)
- Tapered steerer tube 28,6 - 38,1 mm
- Stroke 150 mm
- Stanchion tubes 36 mm
- Axle 15 x 110 mm
- Offset 46 mm
- Wheel size 27,5
- Maximum tire sizes 27,5 x 2,8
- Aluminium design, hard anodized
- Fully servicable and rebuildable
- 2 years limited warranty

## Adjustment:

- Spring rate and progression
- 15-click rebound damping
- 15-click low speed compression damping
- 3-click high speed compression damping

Climb mode

## Purchased parts package:

1 MTB front fork RXF36 m.2 Air

1 axle 15 x 115 mm

1 star-nut

Owners manual

## Part number

FGMTB 3615 2060

## Fits for Mountain bikes

[Universal MTB Air Fork \( - \)](#)

## Price and availability

**1.255,66 €**

1.255,66 € plus % VAT

**Not in stock**

We send you an email as soon as the product is in stock.



## Performance Suspension Guide

Not sure what you need or how to set up your bike? The Öhlins Performance Suspension Guide will help you to find the right product and base set up for you bike.

[Open Performance Suspension Guide](#)

The picture shown can deviate from the product delivered.





Rider weight	Main chamber	Ramp up chamber
50-60 kg (110-132 lbs)	80-90 psi	160-170 psi
60-70 kg (132-154 lbs)	90-100 psi	170-180 psi
70-80 kg (154-176 lbs)	100-110 psi	180-190 psi
80-90 kg (176-198 lbs)	110-120 psi	190-200 psi
90-100 kg (198-220 lbs)	120-130 psi	200-210 psi
100-110 kg (220-243 lbs)	130-140 psi	210-220 psi
110-120 kg (243-265 lbs)	140-150 psi	220-230 psi

## Videos





Single Crown Fork Air Spring Service 34 and 36

## Öhlins Europe

Gottlieb-Daimler-Straße 25  
53520 Meuspath  
Germany

Phone: +49 (0) 2691 -  
937780  
Fax: +49 (0) 2691 - 9377890  
E-Mail: [info.oeu@driv.com](mailto:info.oeu@driv.com)

## Office Hours

Monday to Friday  
08:00 AM to 12:30 PM  
01:30 PM to 05:00 PM

